



Free Standing Cooker

HIT8331



FEATURES

- Multifunktion induktionskomfur
- Display
- Antal funktioner: 8
- Kapacitet ovnrum: 72 L
- Energiklasse: A

Grill

Det perfekte valg til en hurtig grillning. Grill dit favoritmåltid eller færdiggør maden med en sprød skorpe.



Easy clean dør

Med mindre rengøring af ovne er din hobby, vil du elske at høre, at vores Easy clean ovndøre kan skilles ad i et enkelt greb. Alle glaslagene kan adskilles uden brug af værktøj, du skal blot trække op i top beslaget, så er glassene lige til at tage ud og rengøre.

3D Cooking

3d madlavninger, også kaldet multidimensional madlavning, er den nyeste generation af professionel madlavningsteknologi. Her aktiveres alle varmelegemer i toppen, bunden og omkring blæseren, hvorved der opnås den bedst mulige og mest ensartede varmfordeling. Denne funktion giver et perfekt resultat på store stykker kød som f.eks. en hel kalkun eller store stege.

GENERAL	
Type	Free-Standing
Capacity Oven	72 L
Color	White
Oven Type	Multifunctional Cooking
Hob Type	Electric (Induction)
BURNERPLATE	
Rear Left	Ø180mm - 2000/2300W (Max/Boost)
Front Left	Ø180mm - 2000/2300W (Max/Boost)
Rear Right	Ø210mm - 2000/2300W (Max/Boost)
Front Right	Ø145mm - 1600/1800W (Max/Boost)
Burner Plate Surface	Glass
OVEN FUNCTIONS	
Number of Cooking Functions	8 functions
Metal Handle	White
Soft Open / Soft Close Door	NA
Meat Probe	No
Number of glasses in door	3
Light in Oven Cavity	1 x Round Halogen light (Rear)
Doorlock	Mechanical Lock
Display	Led Display
Display Brightness Adjustment	Yes
Pop-In Pop-Out Knobs (PIPO)	No
Knob Color	White
Display Lock	Yes
Steam Cleaning	Simple steam cleaning
Pyrolytic Cleaning	No
Cooling Fan	Yes
Booster	No
OVEN CAVITY AND ACCESSORIES	
Catalytic Back Wall	No
Removable Sideracks	5 levels
Telescopic Rails	NA
Deep Tray	1
Standard Tray	2
Wireshef	1
TECHNICAL INFORMATION	
Energy Efficiency Class	A
Dimensions (WxDxH)	60 x 60 x 90 cm
Niche Dimensions Cabinet (WxDxH)	NA
Niche Dimensions Undercounter (WxDxH)	NA
Cabel	Standard
Cabel lenght	1,2 m
Cabel placement	Rear
Plug type	None
Voltage/Frequency Oven	220-240V~1N;50 Hz



- To ensure that critical air openings are maintained under the product, we recommend that this product is mounted on a solid base and that the feet do not sink into a carpet or soft floor covering. The kitchen floor must be able to support the weight of the unit plus the additional weight of pots, pans, and the food being cooked.
- This product is a Class 1 appliance according to the EN 30-1-1 standard, i.e. it can be placed with its back end and one side to the kitchen walls, kitchen fixtures or equipment of any size. Kitchen furniture or equipment on the other side can only be the same size or smaller.
- The product can be placed with cabinets on both sides, but there must be a minimum distance of 400 mm above the stove and a side clearance of 65 mm between the appliance and all walls, parts or tall cabinets.
- The appliance can also be freestanding. In this case, leave a minimum distance of 750 mm above the surface of the stove.
If a kitchen fan is to be installed above the appliance, the height of the hood should be at least 650 mm, unless otherwise stated.

Installation undercounter